

KNX OPERATING UNITS WITH TOUCH DISPLAY

elsner

NAME	CASA CONNECT KNX	FABRO KNX	KNX TOUCH ONE STYLE	CORLO TOUCH KNX 5IN	CALA TOUCH KNX (3 Models)
Item number	71200	71270	70197	70481, 70475	70800, 70802, 70810, 70812, 70820, 70822
Display size	10.1" (1280 × 800 px)	7" (800 × 480 px)	5.7" (640 × 480 px)	5" (800 × 480 px)	2.3" (320 × 240 px)
Integrated sensors	–	–	Temperature/Humidity	–	T: Temp. TH: Temp./Humidity AQSTH: CO ₂ /Temp./Humidity
Inputs	1× Ethernet (LAN)	–	4× Digital (binary data)	4× Analog/Digital (binary data or temperature sensor T-NTC)	4× Analog/Digital (Binary data or temperature sensor T-NTC)
Additional communication options (additional to KNX)	LAN/WLAN for Internet (browser, remote diagnostics), WLAN for App	–	Radio channel for remote control Remo 8/pro	Model "WL" with WLAN interface	–
Manual operation on Display:					
Shading	✓	✓	✓	✓	✓
Window	✓	✓	✓	✓	✓
Heating/cooling	✓	✓	✓	✓	✓
Ventilation	✓	✓	✓	✓	–
Light	✓ RGB, tunable white	✓ RGB, tunable white	✓	✓	✓ RGB, tunable white
Scenes	✓	✓	–	✓	✓
Operating elements & display surface individually assignable	✓	✓	✓	✓	–
Display of operating elements selectable	–	✓	–	✓	✓
Individual designations (names)	✓	✓	✓	✓	✓
Labelling with symbol	✓	✓	–	✓ (internal library or own files)	–
Screen saver	Off, Clock/Temperature, indiv. pictures, Off when room is dark	Off, Clock		Off, Clock, indiv. pict., Off when room is dark	Off, Clock
Automatic functions:					
Shading	✓	–	✓	✓	–
Window	✓	–	✓	✓	–
Heating/Cooling	✓ (control)	–	✓ (control)	✓ (control)	✓ (control)
Ventilation	✓	–	✓	✓ (control)	T: – TH, AQSTH: ✓ (control)
Light	✓	–	✓	✓	–
Alarm/Security	✓	–	✓	✓	–
Automatic adjustable on the display	✓	–	✓	✓	(only room setpoint temp., mode)
Further bus functions	–	multifunction modules (computers), AND/OR logic	Actuating variable comparators, multifunction modules (computers), AND/OR logic	Limit values, AND/OR logic	Limit values, actuating variable comparators, multifunction modules (computers), AND/OR logic